



## FIREBIRD

SIZES (LOW)	SM	MD	LG	XL	SIZES (HIGH)	SM	MD	LG	XL
<b>A</b> Seat Tube Length (C-T)	375.0	410.0	440.0	470.0	<b>A</b> Seat Tube Length (C-T)	375.0	410.0	440.0	470.0
<b>B</b> Top Tube Length (Eff.)	598.0	624.0	641.0	665.0	<b>B</b> Top Tube Length (Eff.)	597.0	623.0	640.0	664.0
<b>C</b> Head Tube Length	95.0	108.0	118.0	128.0	<b>C</b> Head Tube Length	95.0	108.0	118.0	128.0
<b>D</b> Head Tube Angle	64.0	64.0	64.0	64.0	<b>D</b> Head Tube Angle	64.6	64.6	64.6	64.6
* <b>E</b> Seat Tube Angle (Eff.)	76.0	76.5	77.0	77.0	* <b>E</b> Seat Tube Angle (Eff.)	76.5	77.0	77.5	77.5
<b>F</b> Chain Stay Length	431.0	434.0	438.0	445.0	<b>F</b> Chain Stay Length	430.0	433.0	437.0	444.0
<b>G</b> Bottom Bracket Height	350.0	350.0	350.0	350.0	<b>G</b> Bottom Bracket Height	355.8	355.8	355.8	355.8
<b>H</b> Bottom Bracket Drop	20.0	20.0	20.0	20.0	<b>H</b> Bottom Bracket Drop	14.2	14.2	14.2	14.2
<b>I</b> Standover Height	662.1	672.4	693.5	704.0	<b>I</b> Standover Height	667.2	677.9	698.8	709.4
<b>J</b> Wheelbase	1207.0	1239.0	1267.0	1300.0	<b>J</b> Wheelbase	1206.0	1237.0	1266.0	1299.0
Stack	615.4	627.0	636.0	645.0	Stack	612.0	624.0	633.0	642.0
Reach	445.0	468.0	488.0	510.0	Reach	450.0	473.0	493.0	515.0

\*Effective seat tube angles are calculated at an average saddle height for each size frame.